How To Use The Ultra-Drain Seal Plus®

Protective cover for drains, grates and manholes against accidental spills.

Follow these easy steps to assure maximum effectiveness:

1. Make sure the Ultra-Drain Seal Plus® is the correct size.

For best results, use a Ultra-Drain Seal Plus® which is 6” larger than the outside of the grate.

2. Apply the Ultra-Drain Seal Plus®.


A. Remove all stones, branches, or other debris off the object you desire to cover.
B. Remove the plastic film from the Ultra-Drain Seal Plus® and remember to keep it to re-apply before storage.
C. Place the Ultra-Drain Seal Plus® over the drain, grate, or manhole you desire to seal.
D. To gain a faster seal you may step on the Drain Seal. Never attempt this after spill has reached the drain.

3. Always decontaminate the Ultra-Drain Seal Plus® before reuse or storage.

A. Wash the Ultra-Drain Seal Plus® and its plastic film in warm water with a non-abrasive detergent or petroleum solvent cleaner.
B. Dry both the Drain Seal and plastic film with a cloth and re-apply the plastic film to the Drain Seal.
C. Loosely fold the Drain Seal Plus® and place it back into the box for storage.
D. Store the Ultra-Drain Seal Plus® out of direct sunlight, and at room temperature.

IMPORTANT NOTES:

- Never allow the Ultra-Drain Seal Plus® to touch itself for long periods of time.
- The Ultra-Drain Seal Plus® will become less flexible if stored in cold temperatures.
- Due to the nature of softer urethane, the physical properties of these products may change with exposure to certain environmental conditions like temperature, humidity and UV radiation. Please inspect the stored product regularly to ensure it is in a usable state.



Ultra-Drain Seal

These chemicals are compatible for use with Ultra-Drain Seal:

Acetone*
Aluminum Salts
Ammonia
Barlum Salts
Benzyl Alcohol
Boric Acid Sol.
Butane
Butanol
Calcium Salts
Carbon Dioxide
Chloroform*
Chlorothane VG
Copper Salts
Cyclohexanone
Formaldehyde
Freon
Gasoline
Glycol Ether
Hydrochloric Acid (Med. Conc.)
Hydrofluoric Acid (Med. Conc.)
Hydrogen Peroxide
Kerosene
Methyl Alcohol
Methyl Ethyl Ketone* (MEK)
Methylene Chloride*
Naptha
Nitrogen Oxides
Oil, Mineral
Phenol
Sodium
Sulfuric Acid (Med. Conc.)
Tetrahydrofuran (THF)
Toluene
Trichloroethylene*
Triethylamine
Tropylene Glycol
Turpentine
Water

** Will cause the Ultra-Drain Seal™ to swell temporarily but not degrade.*



Ultra-Drain Seal Plus helps seal off drains to minimize problems!